

NZ LIST OF LIGHTS
(including accompanying notes)

SOUTH ISLAND

(updated to NTM Edition 4, 19 February 2021)

Disclaimer

NZ Light Lists downloaded from <http://www.linz.govt.nz/sea/nautical-information/list-lights> do not meet the requirements as specified in Maritime Rules Part 25 Nautical Charts and Publications (pursuant to Section 36 of the Maritime Transport Act 1994).

ABBREVIATIONS USED IN NEW ZEALAND LIST OF LIGHTS

AHP.....	Above head of passes (in miles)	NNE.....	North Northeast
AIS	Automatic Identification System Station	NNW.....	North Northwest
Al.....	Alternating	NW.....	Northwest
<i>bl</i>	Blast	Oc.....	Occulting
Bu.....	<i>Blue</i>	Oc(. .).....	Group occulting
<i>CALM</i>	Catenary Anchor Leg Mooring	Occas.....	Occasional
Dia.....	Diaphone	(P)	Preliminary
Dir Lt.....	Direction Light	PA.....	Position approximate
E.....	East	PEL.....	Port Entry Light
<i>ec</i>	Eclipse (phase)	Q.....	Quick flashing
ED.....	Existence Doubtful	R.....	<i>Red</i>
ENE.....	East Northeast	Ra refl.....	Radar reflector
ESE.....	East Southeast	Racon.....	Radar responder beacon
Explos.....	Explosive fog signal	RC.....	Circular radio beacon
F.....	Fixed	Ramark.....	Radar beacon
FFI.....	Fixed and flashing	Ro Bn.....	Radio beacon
FFI(. .).....	Fixed and group flashing	Rot.....	Rotating
Fl.....	Flashing	RTE.....	Radar Target Enhancer
Fl(. .).....	Group flashing	S.....	South
<i>fl</i>	Flash (phase)	s.....	Seconds
<i>FPSO</i>	Floating Production Storage and Offloading facility	SAR.....	Search and Rescue
<i>FSO</i>	Floating Storage and Offloading facility	SBM.....	Single Buoy Mooring
<i>FSU</i>	Floating Storage Unit	SE.....	Southeast
G	<i>Green</i>	si	Silence
GRP.....	Glass Reinforced Plastic	Sig Stn.....	Signal Station
HFPB.....	High Focal Plane Buoy	SPM.....	Single Point Mooring
(hor).....	Horizontal	SSE.....	South Southeast
I.....	Interrupted	SSW.....	South Southwest
Intens.....	Intensified sector	SV.....	Sodium vapour discharge lamp <i>orange</i> in colour
Irreg.....	Irregular	SW.....	Southwest
Iso.....	Isophase	(T)	Temporary
<i>Lanby</i>	Large Automatic Navigational Buoy	<i>TALM</i>	Taut Anchor Leg Mooring
Lat.....	Latitude	TD	Fog signal temporarily discontinued
Ldg Lts.....	Leading Lights	TE	Light temporarily extinguished
LED.....	Light Emitting Diode	TR	Racon temporarily discontinued
LFI.....	Long flash	Unintens.....	Unintensified sector
Lit.....	Light (no details known)	UQ.....	Ultra quick flashing
Long.....	Longitude	(var).....	Varying
LPG.....	Liquid Petroleum Gas	(vert).....	Vertical
<i>lt</i>	Light (phase)	Vi.....	<i>Violet</i>
<i>Lt F</i>	Light-float	Vis.....	Visible
Lts in line.....	Lights in line	VQ.....	Very quick flashing
(M).....	Light owned by Maritime New Zealand	W.....	West
M.....	Sea miles	W.....	<i>White</i>
m.....	Metres	Whis.....	Whistle
min.....	Minutes	WNW.....	West Northwest
Mo.....	Morse code light or fog signal	WSW.....	West Southwest
MV.....	Mercury vapour discharge lamp <i>greenish-white</i> in colour	Y.....	<i>Yellow, amber or orange</i>
N.....	North		
NE.....	Northeast		

LAYOUT OF COLUMN HEADINGS IN NEW ZEALAND LIST OF LIGHTS

- Column 1: Contains the number of each light.
- Column 2: Location, name.
Place is printed in CAPITALS.
The names of lights having a range of 15 miles and over are printed in bold type.
- Column 3: Latitude and longitude are given to two decimal places of a minute where data accuracy permits.

IMPORTANT NOTE:

“Positions given are approximate. They are included only to help in the identification of features on charts. It is possible to find differences, especially in longitude, of several tenths of a minute between these positions and those on charts in use, as a result of the variations between geodetic reference systems” (refer page A-8, section 4.3, para. 4, M12 Standardization of List of Lights and Fog Signals 2004. IHO.)

- Column 4: Characteristics.
- Column 5: Elevation in metres.
- Column 6: Range in sea miles, in bold type if 15 miles or more.
- Column 7: Description of structure and its height in metres.
- Column 8: Remarks, including phase, sectors and arcs of visibility.

Refer to www.linz.govt.nz to obtain a full extract from the NZ Nautical Almanac for
General Information relating to the NZ List of Lights

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (5)	Elevation metres (6)	Range miles (7)	Structure Height in metres (8)	Remarks (9)
4180	Cape Farewell. Pillar Point. (M)	40 30.18 172 42.82		FIW 5s	166	9	White metal tower 4	<i>fl 1</i>
GOLDEN BAY / MOHUA								
4182	Farewell Spit. (M) Bush - end Point	40 32.7 173 00.5		FIWR 15s	30	W19 R15	White metal framework tower, orange top 27	<i>fl 0.1.</i> W 117°-297° (180°), R 297°-336.8° (39.8°), W 336.8°-089.5° (112.7°). Obscured 089.5°-117° (27.5°)
TARAKOHE HARBOUR								
4198	- Main Ldg Lts 138° 50'. Front	40 49.6 172 53.9		F Bu	8	7	White Δ on wooden mast	Neon \square
4198.1	- - Rear. 32 m from front			F Bu	10	7	Wooden mast	Neon \square
4199	- E outer mole. Head	40 49.2 172 53.6		FIR 5s	6	3	Round metal tower 2	<i>fl 1.</i> Obscured 201° to 245° until about 2.6 M from harbour entrance
4199.1	- W outer mole. Head	40 49.3 172 53.6		FIG 5s	6	4	Round metal tower 2	<i>fl 1</i>
4201	- E inner mole. Head	40 49.3 172 53.7		Oc R 3s	4	3	Round metal tower 2	<i>ec 1</i>
4201.1	- W inner mole. Head	40 49.34 172 53.68		Oc G 3s	4	3	Round metal tower 2	<i>ec 1</i>
TASMAN BAY / TE TAI-O-AORERE								
4204	Separation Point (M)	40 47.0 172 59.9		FIW 8s	18	8	White metal tower 3	<i>fl 0.5.</i> Vis 099°-328° (229°)
4206	Pitt Head (M)	40 57.0 173 04.0		FI(2)WR 15s	23	W7 R4	Square orange daymark, white stripe 3	<i>fl 1, ec 2, fl 1, ec 11.</i> R 063°-191° (128°), W 191°-337° (146°), R 337°-348° (11°)
MOTUEKA								
4212	- Channel N side	41 08.19 173 01.79		Q G	3	2	Green wooden pile	<i>fl 0.3, ec 0.9.</i> CAUTION: Vessels should not attempt to enter without recent local knowledge
4213	- Training wall. Channel S side	41 08.25 173 01.82		QR	2	2	Pile	<i>fl 0.3, ec 0.9</i>
4214	- Channel N side	41 08.23 173 01.67		Iso G 4s	3	2	Green wooden pile	<i>fl 2, ec 2</i>
MĀPUA								
4220.16	Māpua Port Pile	41 15.00 173 06.74		FIR 2s	3	2	Pile with ladder and band of red retro-reflective tape	
PORT NELSON								
4222	- Schnapper	41 12.19 173 19.42		FI(4)WR 20s	13	W15 R8	Steel column 11	<i>(fl 0.06, ec 3.24) x 3, fl 0.06,</i> <i>ec 10.04.</i> R 031°-047° (16°), W 047°-225° (178°). Ra refl
4223	- Nelson Airport	41 17.9 173 13.5		Aero FIW				
4224	- Port Nelson Landfall Light	41 15.34 173 16.80		FI(2)WR 12s	22	W20 R17	Steel pylon 18	<i>fl 0.2, ec 2.8, fl 0.2, ec 8.8.</i> R 067°-095° (28°), W 095°-216° (121°) FI R on radio masts 2.2 and 3.0 M SW
4225	Ldg Lts 164° 45'. Haulashore Island. Front	41 16.14 173 15.36		Dir WRG	8	W14 R11 G11	White Δ on piles	FG 157.2°-162.2°(5°). AI WG 162.2°-164°(1.8°) W phase increasing with bearing. FW 164°-165.5°(1.5°). AI WR 165.5°-167.2°(1.7°) R phase increasing with bearing. FR 167.2°-177.2°(10°)
4225.1	- - Rear. 600 m from front			F Bu	27	10	White ∇	Neon \square . Vis 130°-200° (70°). Partially obscured 174°-188° (14°)
4225.6	Fairway Beacon	41 14.0 173 14.2		QW	13	9	Black \triangle on black and yellow pile	<i>fl 0.2</i>
4225.8	- Approach Beacon	41 15.44 173 15.18		Oc R 4s	8	5	Red \square on red pile beacon	<i>ec 1</i>

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
4226	- S mole. Off head	41 15.8 173 15.3		Iso G 2s	3	7	Green metal pile	
4227	- Entrance Ldg Lts 135° 25'. Front	41 15.99 173 15.71		F G	6		White △	Neon □
4227.1	-- Rear. 306 m from front			F G	9		White ▽	Neon □. Vis 122°-148° (26°)
4227.4	- Boulder Bank W end No. 1	41 15.73 173 15.45		QR	3	5	Pile beacon	
4227.5	-- No. 2	41 15.79 173 15.55		Iso R 2s	2		Pile	
4227.6	-- No. 3	41 15.82 173 15.65		Iso R 2s	2		Pile	
4227.7	-- No. 4	41 15.81 173 15.74		Iso R 2s	2		Pile	
4228	- Haulashore Island N end. Ldg Lts 270°. Front	41 15.87 173 15.47		F W	3		White ◇ on beacon	
4228.1	---- Rear. 103 m from front			F W	4	3	White △ on beacon	
4230	- Brunt Quay. NW Corner	41 15.59 173 16.27		Iso G 2s			Green metal pole	
4230.15	- Main Wharf SW corner	41 15.74 173 16.11		Iso G 2s	6	3		
4230.2	-	41 15.8 173 16.0		Iso G 2s				
4231	- NW side of channel. No. 5	41 15.75 173 15.85		Iso R 2s	7	2	Red wooden pile	
4231.02	-- No. 6	41 15.7 173 15.9		Iso R 2s	7	2	Red wooden pile	
4231.04	-- No. 7	41 15.54 173 16.08		Iso R 2s	7	2	Red wooden pile	
4231.06	-- No. 8	41 15.46 173 16.17		Iso R 2s	7	2	Red wooden pile	
4231.08	-- No. 9	41 15.38 173 16.27		Iso R 2s	7	2	Red wooden pile	
4231.1	-- No. 10	41 15.37 173 16.40		Mo(A) 8s	7	2	Red ○ on white beacon with red stripes	
BOAT HARBOUR CHANNEL								
4231.2	- No. 12	41 15.26 173 16.53		Iso R 2s	7	2	Red wooden pile	
4231.23	- No. 14	41 15.25 173 16.67		Iso R 2s	7	2	Red wooden pile	
4231.24	- No. 15	41 15.29 173 16.68		Iso G 2s	7	2	Green wooden pile	
4231.26	- No. 16	41 15.4 173 16.8		Iso R 2s	7	2	Red wooden pile	
4231.27	- No. 17	41 15.34 173 16.85		Iso G 2s	7	2	Green wooden pile	
4231.28	- No. 18	41 15.42 173 16.88		FIR 6s	7	2	Red wooden pile	
TASMAN BAY / TE TAI-O-AORERE								
4233	- Croisilles Harbour	41 04.7 173 39.9		FIWR 5s	14	W5 R4	White post on rock 1	W 124°-139° (15°), R 139°-124° (345°)
4234	Okuri Point (M)	40 58.59 173 45.72		FIWR 4s	34	W8 R5	White metal tower 3	fl 0.8. R 160°-210° (50°), W 210°-160° (310°), except where obscured by land
4236	Stephens Island (Takapourewa). N end (M)	40 39.92 174 00.02		FIW 6s	183	18	White metal tower 15	fl 0.1. Vis 054°-350° (296°)
	-- Reserve light					10		
4237	Anatakupu Island (M)	40 53.80 173 52.16		FIW 3s	31	4	Fibreglass Column 2	fl 1
4237.4	Kapowai Bay. S end	40 54.23 173 50.47		FIR 3s	4	1	White square tower	fl 0.3

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
TE AUMITI / FRENCH PASS								
4238	- Channel Point (M)	40 55.44 173 50.10		F WR	3	W10 R7	White house	R 034°-053° (19°), obscured in Waikawa Bay by Two Island Point, W 053°-148° (95°), R 148°-238° (90°)
4240	- Reef (M)	40 55.42 173 50.02		FIW 1.5s	5	4	White beacon 5	<i>fl 0.5</i>
4241	Elmslie Bay. Wharf. Head	40 55.59 173 50.65		FIG 3s	3	1	Cargo Shed	
CHETWODE ISLAND								
4242	Ninepin Rock (M)	40 54.86 174 03.30		FIW 4s	17	8	White metal tower 3	<i>fl 0.8</i>
4242.05	Oke Rock	40 55.55 174 01.63		FIG 10s	6	3	Green Δ on green beacon 7	<i>fl 1.</i> Ra refl
PELORUS SOUND / TE HOIERE								
4242.1	- Maud Island (Te Hoiere). NE Point	41 00.99 173 54.45		FIW 15s	24	10	White post 2	Vis 088°-031° (303°)
4242.15	Dart Rock	41 02.8 173 49.0		FI(2)W 20s	3	5	Black \bullet on white post, Black with red bands	<i>fl 0.5, ec 1, fl 0.5, ec 18</i>
4242.17	Flax Point	41 05.7 173 47.0		FIW 10s	9	2	White post 2	<i>fl 0.5</i>
4242.2	Tawero Point Orchard	41 03.8 173 57.0		FIW 5s	9	5	White post 2	Vis 099°-320° (221°)
4242.3	Tawero Point. S	41 04.0 173 56.8		FIW 10s	11	5	White post 2	Vis 217°-052° (195°)
4242.4	Turn Point. N	41 08.4 173 52.3		FI(2)W 15s	6	5	White post 2	Vis 040°-233° (193°)
4242.5	Turn Point. S	41 08.7 173 52.0		FIW 10s	7	5	White post 2	<i>fl 0.5.</i> Vis 357°-190° (193°)
4242.6	One Tree Point. N	41 11.5 173 51.9		FIW 10s	7	5	White post 2	Vis 178°-008° (190°)
4242.7	One Tree Point. S	41 11.8 173 51.9		FIG 10s	6	3	White post 2	Vis 187°-022° (195°)
4242.9	Black Point	41 14.5 173 51.0		FIW 5s	2	5	White post 2	<i>fl 0.5</i>
HAVELOCK HARBOUR								
4243	- No. 1	41 14.83 173 50.77		FIG 2s	2	3		<i>fl 0.5</i>
4243.1	- No. 3	41 15.19 173 50.35		FIG 3s	2	3	Green pile beacon	<i>fl 0.5</i>
4243.15	- No. 5	41 15.36 173 49.93		FIG 4s		3		<i>fl 0.5</i>
4243.17	- No. 7	41 15.51 173 49.13		FIG 5s	2	3	Green pile beacon	<i>fl 0.5</i>
4243.2	- No. 2	41 15.58 173 48.68		FIR 2s	2	3	Red pile beacon	<i>fl 0.5</i>
4243.27	- No. 4	41 15.60 173 47.81		FIR(2) 4s		3		<i>fl 0.5, ec 1, fl 0.5, ec 2</i>
4243.3	- Shag Point	41 15.54 173 47.80		FIW 3s	2	3	White pile beacon	<i>fl 0.5</i>
4243.35	Havelock Approach Ldg Lts 104°. Front	41 15.81 173 47.43		F.Bu	3	2	White Δ on white wooden pole	
4243.36	- Rear	41 15.83 173 47.53		F.Bu	5	2	White ∇ on white wooden pole	
4243.4	- No. 9	41 15.76 173 47.29		FIG(2) 4s	3	3	Green pile beacon	
4243.44	- No. 6	41 15.74 173 47.00		FIR(2) 5s		3	Red pile beacon	
4243.48	- No. 11	41 15.72 173 46.73		FIG(2) 5s		3	Green pile beacon	
4243.5	- No. 8	41 15.77 173 46.73		FIR(2) 6s	2	3	Red pile beacon	<i>fl 0.5</i>
4243.504	- No. 10	41 15.79 173 46.61		FIR 3s	1	3	Red wooden pile beacon	
4243.506	- No. 12	41 15.92 173 46.46		FIR 3s	2	3	Red wooden pile beacon	
4243.508	- No. 14	41 15.95 173 46.37		FIR 3s	1	3	Red wooden pile beacon	
4243.51	Cullen Point	41 15.98 173 46.34		FIR 3s	3	3	White post 2	<i>fl 0.3</i>

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
4243.517	- No. 13	41 15.95 173 46.27		FIG 3s		3		
4243.6	- No. 15	41 16.11 173 46.28		FIG 3s	4	3	Green wooden pile beacon	<i>fl 0.5</i>
4243.601	- No. 17	41 16.19 173 46.27		FIG 3s	2	3	Green wooden pile beacon	
4243.603	- No. 19	41 16.27 173 46.25		FIG 3s	2	3	Green wooden pile beacon	
4243.605	- No. 21	41 16.36 173 46.24		FIG 3s	2	3	Green wooden pile beacon	
4243.609	- No. 23	41 16.43 173 46.23		FIG 3s	2	3	Green wooden pile beacon	
4243.61	- Johnson Light	41 16.43 173 46.27		FIR 3s		3	Post 3	<i>fl 0.5</i>
COOK STRAIT								
4244	Cape Jackson (M)	40 59.72 174 18.82		FI(3)W 20s	87	9	White metal tower 4	<i>(fl 1, ec 1) x 2, fl 1, ec 15.</i> Vis 050°-003° (313°). May be obscured by cliffs within 50m of the light
4244.5	-- (Rock)	40 59.36 174 19.18		FIW 4s	15	3	White tower on concrete base 15	<i>fl 0.4</i>
4246	The Brothers (M)	41 06.19 174 26.47		FIW 10s	79	19	White wooden tower 12	<i>fl 0.1</i>
	- Reserve light			FIR 10s	70	10	Same structure	<i>fl 1.5.</i> Vis 164.5°-169.5° (5°) over Cook Rock, but obscured within 0.8 M
				FIR 10s	74	10	Same structure	<i>fl 1.5.</i> Vis 008°-014° (6°) over awash rocks
QUEEN CHARLOTTE SOUND / TŌTARANUI								
4248	- Motuara Island. S end	41 05.95 174 16.58		FI(2)W 10s	28	8	White metal framework tower 5	<i>fl 0.4, ec 1.6, fl 0.4, ec 7.6</i>
4248.5	Scott Point	41 08.54 174 13.21		FI(2)G 5s	3	4	Green Δ on white pile beacon	Obscured 110° -210° (100°)
4249	-Edgecombe Point	41 09.26 174 12.04		FIW 10s	3	5	White post 3	<i>fl 0.5</i>
4249.5	- Farnham Point	41 10.35 174 12.03		LFI.WRG 10s	6	10	White metal tower	<i>fl 2, ec 8.</i> G 218.4°-220.5° (2.1°), W 220.5°-223.7° (3.2°), R 223.7° -225.8° (2.1°)
4250	- Kurakura Point	41 10.98 174 12.15		FI(3)W 15s	28	10	White metal column, red top 3	<i>(fl 0.8, ec 1.2) x 2, fl 0.8,</i> <i>ec 10.2</i>
4251	Snake Point	41 12.20 174 10.16		Q(6) + LFI W 15s	3	1	Black ∇ on yellow and black beacon 4	
4252	- Dieffenbach Point	41 13.90 174 08.78		FIW 3s	15	6	White tower 3	<i>fl 0.3</i>
4253	- Luke Rock	41 13.19 174 08.30		FIG 5s	3	5	Green Δ on green column	<i>fl 0.3</i>
4253.5	- Allports Island	41 14.35 174 03.44		Q(5)W 10s	3	5	White post 2	<i>(fl 0.3, ec 0.7) x 4, fl 0.3,</i> <i>ec 5.7</i>
4254	- The Snout	41 15.03 174 02.91		FI(3)W 10s	14	7	White post 2	<i>fl 0.5, ec 1.0, fl 0.5, ec 8</i>
4254.5	-- Waikawa Bay Marina. S Breakwater	41 15.89 174 02.36		Oc WRG 3s	5	8	White metal post 4	<i>ec 0.5.</i> G 213.2°-218° (4.8°), W 218°-228.2° (10.2°), R 228.2°-233.2° (5°)
4254.6	-- N breakwater	41 15.85 174 02.38		FIG 3s	3	2	White metal post 3	<i>fl 0.5</i>
4255	- Picton Point	41 15.25 174 02.21		FIR 2.5s	3	2	White post 3	<i>fl 0.5</i>
PICTON HARBOUR								
4256	- Mabel Island. S Point	41 16.16 174 00.89		FIW 2s	4	4	White concrete post 4	<i>fl 0.3.</i> Vis 182.2°-112.8° (290.6°)
4256.2	Picton Harbour Approaches	41 16.60 174 00.53		FIG 3s	2	1		<i>fl 0.3</i>
4256.7	- Shelly Beach	41 16.91 174 00.71		FIR 3s	3	5	White metal post	<i>fl 0.3</i>

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
4256.85	- Shelly Beach Breakwater	41 17.22 174 00.53		FIR 6s	5	2	White metal post 3	<i>fl 0.5</i> QBu Occas light on separate pole supporting marina sign
4256.9	- Picton Floating Breakwater	41 17.26 174 00.50		FIG 4s	2	5	White metal post on floating breakwater 2	<i>fl 0.5</i>
4257	- Waitohi Wharf. Head	41 16.95 174 00.39		F R Q Bu	7 20	6 5	Metal framework flood-lighting tower Same structure	Occas warning light is exhibited when large vessels are manoeuvring at Picton Wharves
4257.5	- Breakwater	41 17.4 174 00.5		F G				
4257.8	- Ldg Lts 176° 05'. Front	41 17.30 174 00.49		F G	4	2	Concrete pile 3	
4257.81	- - Rear. 20 m from front	41 17.31 174 00.48		F G	6	2	Concrete pile 4	
4258	- Ferry Terminal No.1 Wharf. Head	41 17.05 174 00.40		F G	8		Mast 4	
4258.2	- - Root	41 17.10 174 00.33		F G	10		On ferry terminal	
4259	- - No. 2 Wharf. Head	41 17.00 174 00.39		F R	6		Mast 3	
4259.2	- - - Root	41 17.07 174 00.30		F R	10		Mast 6	
4260	- Wedge Point	41 15.50 174 00.67		Mo(A) 8s	8	5	White post 2	<i>fl 0.2, ec 1.4, fl 3, ec 3.4</i>
4260.2	Shakespeare Bay. Inner	41 16.33 174 00.24		Q(4)R 6s	2	3	White post 2	<i>(fl 0.4, ec 0.6) x 3, fl 0.4, ec 2.6</i>
4260.3	- Shakespeare Bay. No. 3	41 16.31 173 59.87		LFI G 5s	2	3	White post 1	
4260.4	Shakespeare Bay. Outer	41 15.96 174 00.28		Q(5)G 10s	2	3	White post 2	<i>(fl 0.3, ec 0.7) x 4, fl 0.3 ec 5.7</i>
TORY CHANNEL / KURA TE AU								
4261	- Houhou Light	41 15.23 173 58.44		FIG 5s	2	2	Green Δ on pillar	
4262	- W Head	41 12.80 174 18.88		Mo(N)WR 10s	46	8	White tower 4	<i>fl 1, ec 1, fl 0.5, ec 7.5.</i> W 090.2°-247.5° (157.3°), R 247.5°-270.9° (23.4°), W 270.9°-09.1° (98.2°), R 09.1°-052.2° (43.1°)
4264	- Arapawa Island Ldg Lts 311° 45'. Front	41 12.16 174 18.30		Q W	7	11	White Δ orange stripe 6	
4264.1	- - - Rear. 130 m from front	41 12.10 174 18.22		Iso W 2s	27	11	White Δ orange stripe 6	
4264.5	- Wheki Rock	41 12.44 174 18.31		FIG 3s	2	2	Green beacon	<i>fl 0.3</i>
4265	- E Head. Dir Lt	41 12.62 174 19.41		Dir WRG	35	3	Wooden post 1	F G 083.1°-087.0° (3.9°). AI WG 087.0°-090.7° (3.7°). F W 090.7°-095.1° (4.4°). AI WR 095.1°-098.8° (3.7°). F R 098.8°-103.0° (4.2°) R light on mast 2.3 M NE
4266	- Scraggy Point	41 12.90 174 18.32		FI(2)W 10s	19	5	White post 2	<i>fl 0.5, ec 2, fl 0.5, ec 7</i>
4266.1	- Motukina Point	41 14.64 174 15.29		FIR 5s	14	4	White post 2	<i>fl 0.5</i>
4267	- Te Uira-karapa Point. W	41 14.25 174 15.04		FI W 5s	8	6	White metal pole 3	<i>fl 0.4</i>
4267.1	- - E	41 14.21 174 15.23		FIG 3s	18	4	White wooden pole 2	An old light tower (3 m) is situated close W
4267.4	- Arrowsmith Point	41 14.61 174 12.05		FI(4)W 15s	4	5	White post	<i>(fl 0.5, ec 1) x 3, fl 0.5, ec 10.</i> Vis 081.1°-270.4° (189.3°)
4268	- Ruaomoko Point. E	41 14.62 174 10.00		FI(3)W 10s	22	5	White post 2	<i>(fl 0.5, ec 1) x 2, fl 0.5, ec 6.5</i>
4268.2	- - W	41 14.51 174 09.66		Q W	8	5	White post 2	
4268.21	- Otamango Point	41 15.06 174 09.50		FIR 3s	6	4	White post 2	<i>fl 0.3</i>

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
COOK STRAIT								
4268.3	- Fighting Bay. Prohibited Anchorage and Fishing Area. N limit.	41 18.41 174 14.09		Fl(4)WR 20s	189	W7 R4	White Δ on beacon orange stripe	<i>fl 1, ec 0.5</i> x 3, <i>fl 1, ec 14.5.</i> W 221°-263° (42°), R 263°-310° (47°). Daymark 263° 100 m marks N limit of cable area
4268.4	- - - S limit.	41 20.14 174 10.45		L Fl(2)WR 20s	117	W7 R5	White Δ on beacon orange stripe	<i>fl 2, ec 0.5, fl 2, ec 15.5.</i> R 271°-301° (30°), W 301°-051° (110°). Daymark. 301°-200 m marks S limit of cable area
4269	Robertson Point	41 21.08 174 07.11		Fl W 5s	16	5	White concrete column 2	<i>fl 0.5</i>
4272	Blenheim (Aerodrome)	41 30.9 173 52.3		Aero Al WG 3.7s				F R on radio mast 4 M E
4273	-	41 32.6 173 48.1		Aero Oc R				
4274	Cape Campbell (M)	41 43.8 174 16.5		Fl W 15s	47	19	White metal tower, black bands 22	<i>fl 0.1.</i> Obscured by land when bearing more than 010° RC
KAIKŌURA PENINSULA								
4275	- Point Kean (M)	42 25.45 173 42.94		Fl(2)W 15s	41	9	Yellow metal tower 4	<i>fl 1, ec 2, fl 1, ec 11</i>
4276	- N Wharf. Ldg Lts 221° 35'. Front	42 24.77 173 42.16		F G	6		Orange steel post 4	
4276.1	- - - Rear. 91 m from front	42 24.81 173 42.12		F G	8		Orange steel post 7	
4277	- Kaikōura S Breakwater Head	42 25.56 173 40.85		Iso G 2s	6	6	Steel post, black and white bands 3	
4279	Point Gibson (M)	42 53.2 173 19.0		Fl W 10s	76	10	Red metal tower, white bands 3	<i>fl 1.</i> Vis 202°-027° (185°)
4282	Motunau River. Entrance. Ldg Lts. Front	43 03.1 173 04.6		F R	6	3	Mast	CAUTION: Vessels should not attempt to enter without local knowledge
4282.1	- - Rear. 73 m from front			F R	12	3	Mast	
LYTTELTON HARBOUR/WHAKARAUPŌ								
4286	- Godley Head	43 35.22 172 48.43		L Fl(3)W 26s	127	17	Grey steel pole 4	<i>(fl 2, ec 4) x 2, fl 2, ec 12.</i> Vis 180°-330° (150°)
4289.5	- North Stake Ldg Lts Front Stbd No. 31	43 36.80 172 42.82		F G	6	5	Green Δ on green piled beacon with platform 6	
4289.6	- - Rear Stbd No. 33	43 36.89 172 42.07		F G	6	5	Green Δ on green piled beacon with platform 6	
4290	- Centre Stakes Ldg Lts Front Lead No. 35.	43 36.85 172 42.83		Q W	8	6	White piled beacon with platform, orange \square daymark 8	<i>fl 0.5, ec 0.5.</i>
	- Dir Lt 260.65°			Dir WRG	8	10	Same structure	F G 259.25° - 260.35° (1.1°) F W 260.35° - 260.95° (0.6°) F R 260.95° - 262.05° (1.1°) Light oscillates at the margins of the white sector
				By day		W 5 R 3 G 3		
4290.1	- - Rear Lead No. 37	43 36.94 172 42.08		Iso W 4s	18	7	White piled beacon with platform, orange \square daymark 18	<i>fl 2.0, ec 2.0</i>
4290.05	- South Stakes Ldg Lts Front Port No. 36	43 36.90 172 42.84		F R	6	5	Red \square on red piled beacon with platform 6	
4290.06	- - Rear Port No. 38	43 36.99 172 42.09		F R	6	5	Red \square on red piled beacon with platform 6	

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (5)	Elevation metres (6)	Range miles (7)	Structure Height in metres (8)	Remarks (9)
4291	- Parson Rock Beacon	43 36.81 172 45.13		Fl(2)R 10s	7	4	Red □ on red pile beacon	fl 0.5, ec 1, fl 0.5, ec 8
4293	- Sticking Point. Breakwater. Head	43 36.62 172 44.01		Fl(2)G 5s	8	5	White pile	
4295	- North Turn Off Ldg Lts Front Lead No. 21	43 36.55 172 42.89		F R	10	9	White tubular tower with platform, orange △ daymark 10	Vis 293.53° - 311.53° (18°)
4295.1	-- Rear Lead No.23	43 36.55 172 42.88		By day F R	10	9	White tubular tower with platform, orange ▽ daymark 14	Vis 293.53° - 311.53° (18°)
4296	- Centre Turn Off Front Lead No. 22	43 36.60 172 42.78		By day F Bu	10	9	Blue tubular tower with platform, blue △ daymark 10	Vis 293.53° - 311.53° (18°)
4296.1	-- Rear Lead No. 24	43 36.59 172 42.77		By day F Bu	14	9	Blue tubular tower with platform, blue ▽ daymark 14	Vis 293.53° - 311.53° (18°)
4299	- West Mole Port Beacon No. 30	43 36.51 172 42.96		By day Q R		3	Lattice beacon, white and black squared	fl 0.3, ec 0.7
4300	- East Mole Stbd Beacon No. 29	43 36.55 172 43.06		Q G	6	3	Green △ on piled beacon with platform 6	fl 0.3, ec 0.7
4301	- South Turn Off Front Lead No. 26	43 36.63 172 42.66		F R	10	9	White tubular tower with platform, orange △ daymark 10	Vis 293.53° - 311.53° (18°)
4301.1	-- Rear Lead No. 28	43 36.63 172 42.65		By day F R	14	9	White tubular tower with platform, orange ▽ daymark 14	Vis 293.53° - 311.53° (18°)
4303	- Purau Bay Ldg Lts Front Lead No. 40	43 36.81 172 46.44		By day QW	8	6	White piled beacon with platform, orange □ daymark 8	fl 0.5, ec 0.5
				Dir WRG	8	10	Same structure	F G 238.81° - 241.06° (2.25°) F W 241.06° - 241.56° (0.5°) F R 241.56° - 243.81° (2.25°) Light oscillates at the margins of the white sector
4303.1	-- Rear Lead No. 42	43 37.13 172 45.64		By day Iso W 4s	18	7	White piled beacon with platform, orange □ daymark 18	fl 2.0, ec 2.0
4310	Steep Head (M)	43 44.8 173 07.6		By day Fl W 5s	156	19	White metal tower 4	fl 0.1. Vis 161°-001° (200°). Owing to its elevation the light is liable to be obscured by fog and mist
AKAROA HARBOUR								
4314	- Akaroa Head (M)	43 53.5 172 58.7		Fl W 10s	68	19	White fibreglass tower 3	fl 0.1. Vis 262°-116° (214°) but obscured from seaward by Timutimu Head when bearing more than 071°
4315	-- Ldg Lts 330° 36'. Front	43 49.11 172 54.21		F G	10	7	Wooden power pole 7	
4315.1	--- Rear. 0.81 M from front	43 48.41 172 53.66		F G	83	7	Wooden pole 7	

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
4316	- Green Point. W end of reef	43 48.91 172 56.80		FIG 5s	4	2	White wooden post 5	
4318	- Childrens Bay Ldg Lts 058° 36'. Front	43 48.11 172 58.04		F G	7	5	On street light, red and yellow quarters on circular daymark	Neon □
4318.1	- - - Rear	43 48.09 172 58.08		F G	10	5	On street light, red and yellow quarters on circular daymark	Neon □
TIMARU HARBOUR								
4322	- Fairway Beacon	44 22.83 171 19.37		Mo(A)W 10s	8	9	White beacon, red stripes	
4323	-	44 13.5 171 26.0		Oc Y 5s	9	2	White △ on wooden pile 2	
4324	- Airport	44 18.3 171 13.5		Aero FIW 3.7s	31	15		<i>fl 0.2.</i> Location beacon
4328	- Ldg Lts 267° 35'. Front	44 23.09 171 15.53		F G	16	5	Orange △ on white concrete post	Neon □
4328.1	- - Benvenue Cliff. Middle. 0.53 M from front	44 23.11 171 14.78		Dir WR G	25	W21 R17 G17	Orange △ on beacon 4	F G 265.0°-266.5° (1.5°). AI WG 266.5°-267.2° (0.7°) W phase increasing with bearing. F W 267.2°-268.0° (0.8°). AI WR 268.0°-268.7° (0.7°) R phase increasing with bearing. F R 268.7°-270.2° (1.5°) Neon □
				F G <i>By day</i>	25	10 5		
4328.2	- - Rear. 210 m from middle	44 23.12 171 14.62		F G	30	7	Orange △ on beacon 4	Neon □
4329	- Eastern Extension Mole. Spur Breakwater Head	44 23.16 171 16.01		FIR 5s	17	11	Tower	<i>fl 1.</i> F R lights on radio mast 2.5 M N
4329.4	- Outer N Mole. Head	44 23.19 171 15.72		FIG 10s	10	6	White wooden mast 8	
4330	- Lts in line 228°. E mole. Head. Front	44 23.37 171 15.62		F R	7	2	Metal box 4	Neon □. Vis 003°-244° (241°)
4330.1	- - No. 2 Wharf. Root. Rear. 640 m from front	44 23.59 171 15.29		F R	20	2	Metal box on floodlit tower	Neon □
4331	- War Memorial	44 23.86 171 15.15		F W	44	14	Mast	
				<i>By day</i>		10		
4332	- Inner N Mole. Head	44 23.30 171 15.62		FIG 2s	6	5	White lattice tower inclined 45° from vertical	<i>fl 0.3.</i> Electric lights in railway yard are visible from seaward especially when approaching from S
4335	- No. 3 Wharf. Head Lts in line 228°. Front	44 23.47 171 15.35		F G	6	4	Metal box	Neon □
4335.2	- - Near root. Rear. 230 m from front	44 23.55 171 15.23		F G	20	4	Metal box	Neon □ TE 2020
4340	Tuhawaiki Point (M)	44 26.58 171 15.64		L FIW 10s	29	9	White metal tower 9	<i>fl 2</i>
OAMARU HARBOUR								
4348	- Breakwater. Head	45 06.34 170 58.83		FIR 5s	8	5	Framework tower	<i>fl 0.3</i>
4350	- Holmes Wharf. Head	45 06.36 170 58.68		F G	4	2	Lamp Post	
4358	Moeraki. Ldg Lts 216° 31'. Front	45 21.8 170 50.8		QW	11	6	Mast 4	
4358.1	- - Rear. 500 m from front			Iso W 4s	51	6	Mast 4	
4359	- Wharf. Head	45 21.6 170 51.2		Iso R 3.5s	5	2	White post, red top	
4360	- Katiki Point (M)	45 23.68 170 52.09		Iso W 12s	56	14	White wooden tower 8	Vis 181°-018° (197°)
4362	Heyward Point	45 45.37 170 41.53		FIWR 5s	25	W9 R7	White tower 4	<i>fl 0.7.</i> W shore-259°, R 259°-306.5° (47.5°)

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (3)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
OTAGO HARBOUR								
4363	Fairway Beacon	45 45.07 170 43.62		Fl(2)R 5s	9	5	Red ◻ on pile beacon, pivoted at base	fl 0.5, ec 1, fl 0.5, ec 3
4364	Taiaroa Head	45 46.42 170 43.73		LFl(2)W 18s	60	18	White stone tower 12	fl 2, ec 4, fl 2, ec 10. Vis 158°-300° (142°) Disused Sig. Stn. FR lights on mast 7.5M WSW
4365	N mole	45 46.24 170 43.18		Fl(3)W 5s	9	5	Black ◊ on black metal column with yellow band	Ra refl
4366	Approach Channel. Dir Lt 186° 09'	45 47.90 170 43.11		Dir WRG	19	W21 R17 G17	Red △ on white tower 5	F G 183.65°-185.1° (1.45°). Al W G 185.1°-185.45° (0.35°) W phase increasing with bearing. F W 185.45°-186.85° (1.4°). Al W R 186.85°-187.2° (0.35°) R phase increasing with bearing. F R 187.2°-188.65° (1.45°). An overspill of white light is visible at night to eastward and westward of the fixed red and green sectors. Vessels should ensure they have crossed the red and green sectors before turning on to the leading line. Range 5M when sighted outside the main Dir Lt Sectors
						<i>By day</i>	4	
LOWER HARBOUR								
4366.9	No. 1	45 46.50 170 43.21		Fl G 3s	3	2	Green △ on green beacon	
4367	No. 1A	45 46.82 170 43.14		Fl(2)G 5s	3	3	Green △ on green beacon	Ra refl
4367.1	Harington Point	45 47.00 170 43.39		F Y Oc R 10s	3	4 2	Red metal beacon	177°-182° (5°) ec 1
4367.12	Spit Tide Gauge Pile	45 47.16 170 43.12		Oc G 4s	3	3	Green △ on steel pile	
4367.2	No. 2	45 47.27 170 43.39		Fl R 3s	3	3	Red ◻ on red beacon	Ra refl
4367.3	No. 3	45 47.36 170 43.09		Fl(2)G 4s	3	3	Green △ on green beacon	Ra refl
4367.4	No. 4. Groyne. Head	45 47.44 170 43.31		Fl(2)R 4s	3	3	Red ◻ on red tripod beacon	Ra refl
4367.5	No. 5	45 47.50 170 42.95		Fl(3)G 6s	3	3	Green △ on green beacon	(fl 0.5, ec 1) x 2, fl 0.5, ec 2.5. Ra refl
4367.6	No. 6. Groyne. Head	45 47.61 170 43.11		Fl(3)R 6s	3	3	Red ◻ on red beacon	Ra refl
4367.7	No. 7	45 47.60 170 42.76		Fl G 3s	3	3	Green △ on green beacon	Neon ◻. Ra refl
4367.8	No. 8. Groyne. Head	45 47.73 170 42.87		Fl R 3s	3	3	Red ◻ on red tripod beacon	Ra refl
4367.9	No. 9	45 47.67 170 42.46		Oc G 4s	5	3	Green △ on green beacon	ec 1. Ra refl
4368	No. 10. Groyne. Elbow	45 47.80 170 42.48		Oc R 10s	3	2	Red ◻ on red beacon	ec 1. Ra refl
4368.2	No. 11	45 47.65 170 41.81		Fl G 2.5s	3	1	Green △ on green beacon	Ra refl
4368.3	No. 12	45 47.79 170 41.76		Fl R 2.5s	3	1	Red ◻ on red beacon	Ra refl
4368.4	No. 13	45 47.48 170 40.81		Fl(2)G 5s	3	3	Green △ on green beacon	Ra refl
4368.45	No. 13A Ldg Lts 283° 15'. Front	45 47.46 170 40.21		F G	3	3	Green △ on green beacon	Neon ◻. Ra refl
4368.46	- Rear. 870 m from front	45 47.36 170 39.57		Q W	5	5	White △ on tripod beacon	fl 0.5, ec 0.5

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
4368.5	No. 14	45 47.63 170 40.75		FI(2)R 4s	3	3	Red □ on red beacon	Ra refl
4368.6	No. 15	45 47.55 170 39.83		FI G 3s	3	3	Green △ on green beacon	Ra refl
4368.7	No. 16	45 47.61 170 40.25		FI(3)R 6s	3	3	Red □ on red beacon	Ra refl
4368.72	No. 16A	45 47.69 170 39.92		FI R 3s	3	3	Red □ on red beacon	Ra refl
4368.8	No. 17 – Off Pulling Point	45 47.76 170 39.39		F G	3	3	Green △ on green tripod beacon	Neon □. Ra refl
4368.9	No. 18	45 47.89 170 39.47		FI(2)R 5s	3	3	Red □ on red pile beacon	Ra refl
4368.95	No. 18A	45 47.99 170 39.04		Oc R 4s	3	3	Red □ on red beacon	Ra refl
4369	No. 19 – Off Acheron Head	45 47.90 170 38.74		F G	3	3	Green △ on green tripod beacon	Neon □. Ra refl
4369.1	No. 19A	45 47.90 170 38.47		FI(3)G 6s	3	3	Green △ on green pile beacon	Ra refl
4369.2	No. 20	45 48.04 170 38.50		FI(3)R 6s	3	3	Red □ on red beacon	Ra refl
4369.22	No. 20A	45 48.11 170 38.30		FI R 3s	3	3	Red □ on red tripod beacon	Ra refl
4369.5	No. 21	45 47.93 170 38.33		FI G 3s	3	3	Green △ on green pile beacon	Ra refl
4369.52	No. 21A	45 48.00 170 38.14		F G	3	3	Green △ on green pile beacon	Neon □. Ra refl
4369.6	No. 22	45 48.20 170 38.14		FI(2)R 4s	3	3	Red □ on red	Ra refl
4369.7	Ldg Lts 012°30'. Front. No. 23	45 48.09 170 37.99		Oc G 4s	3	3	Green △ on green beacon	ec 1. Ra refl
4369.71	- Rear. 520m from front. Deborah Bay	45 47.81 170 38.08		Q W	3	3	Black and white pile beacon	fl 0.5, ec 0.5
4369.8	No. 24	45 48.31 170 38.02		FI R 3s	4	3	Red □ on red beacon	Ra refl
4369.82	No. 24A	45 48.48 170 37.95		FI(2)R 4s	4	3	Red □ on red beacon	Ra refl
4369.83	No. 25 – Off Rocky Point	45 48.27 170 37.79		F G	3	6	Green △ on green tripod beacon 3	Neon □. Ra refl
				By day Dir RY		2		F R 345°-350° (5°). F Y 350°-355° (5°)
4369.84	Careys Bay. Fishing Berths. SE head	45 48.50 170 37.58		3 F G(vert)	3	1	Pole on wharf	
4369.85	Boiler Point	45 48.49 170 37.62		FI R 3s	3	2	Red pile 3	
4369.86	Multi Purpose Berth. N end	45 48.51 170 37.70		FI G	5			
4370		45 48.63 170 38.01		FI R 3s	3	1	Red □ on red beacon	Ra refl
PORT CHALMERS								
4370.2	No. 27	45 48.49 170 37.70		Oc G 10s	3	1	Green pile beacon	ec 2.5.
4370.25	Container Terminal Wharf. NE end	45 48.73 170 37.59		4 F W(hor)				
4370.26	Ldg Lts 191°30'. Front.	45 48.87 170 37.72		F Bu	15	2		
4370.261	- Rear. 145m from front.	45 48.94 170 37.70		F Bu	15	2		
4370.27	Beach Street Wharf. E end	45 48.83 170 37.75		F G				Neon □
4370.3	No. 28	45 48.81 170 37.99		FI(2) R 4s	3	3	Red □ on red beacon	Ra refl
4370.74	No. 29	45 48.99 170 37.80		F G	3	3	Green △ on green pile	Neon □
4370.9	No. 30	45 49.06 170 37.98		FI R 3s	3	1	Red □ on red beacon	Ra refl

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (5)	Elevation metres (6)	Range miles (7)	Structure Height in metres (8)	Remarks (9)
4371	Wharf - SE corner	45 49.16 170 37.75		VQ(3)W	3	1	⬆ on yellow and black beacon 3	
4371.5	Wharf – off SW corner	45 49.20 170 37.61		VQ(6) + LFIW 15s	3	1	∇ On yellow and black beacon 3	Ra refl
4372	Ldg Lts 028° 20'. No. 32. Front	45 49.24 170 37.92		Q(2)R 4s	3	1	Red □ on red beacon, white band	Ra refl
4372.1	- Rear. 170 m from front	45 49.16 170 37.98		QR	3	1	Red beacon	
4372.2	Ldg Lts 044° 43'. Halfway Islands Passage. Front	45 49.39 170 37.93		FI(2)Y 4s	3	1	Black pile beacon, White △	
4372.21	- Rear. 230 m from front	45 49.30 170 38.05		QY	3	1	Black pile beacon, White ∇	
UPPER HARBOUR								
4372.4	Ldg Lts 208° 20'. No. 2A. Front	45 49.82 170 37.47		FI(2)R 4s	3	1	Red double pile beacon	
4372.5	- Rear. 100 m from front	45 49.86 170 37.44		QR	3	1	White	
4373	Goat Island No. 1	45 49.56 170 37.62		QG	3	1	Pile beacon	
4373.2	No. 2 Quarantine Island/Kamau Taurua	45 49.61 170 37.69		QR	3	2	Pile beacon	
4373.25	No. 33	45 49.44 170 37.71		FI(3)G 6s	3	3	Green △ on green pile beacon	(fl 0.5, ec 0.5) x 2, fl 0.5, ec 3.5
4373.3	No. 3	45 49.71 170 37.23		FI(2)G 5s	3	1	Green △ on green pile beacon	
4373.4	No. 4	45 49.81 170 37.25		FI(2)R 5s	3	1	Red □ on pile	
4373.44	No. 5	45 49.74 170 36.87		QG	3	1	Green △ on green beacon	
4373.6	No. 6	45 49.83 170 36.88		QR	3	1	Red □ on pile	
4373.7	No. 7	45 49.77 170 36.51		FI(2)G 5s	3	1	Green △ on green beacon	
4373.8	No. 8	45 49.86 170 36.54		FI(2)R 5s	3	1	Red □ on pile	
4373.9	No. 8A	45 49.90 170 36.32		FI(3)R 6s	3	1	Red □ on pile	
4374	Kilgours Point. No. 9	45 49.88 170 36.14		FI(3)G 6s	3	1	Green △ on green beacon	
VICTORIA CHANNEL								
4374.1	- No. 11	45 50.00 170 35.82		QG	3	1	Green △ on green pile beacon	
4374.12	- No. 12	45 50.06 170 35.87		QR	3	1	Red □ on pile beacon	F R lights on radio masts 3.1 M SSW
4374.125	- No. 13	45 50.04 170 35.72		FI(2)G 5s	3	1	Green △ on green beacon	
4374.13	- No. 15	45 50.07 170 35.62		FI(3)G 6s	3	1	Green △ on green beacon	
4374.14	- No. 16	45 50.14 170 35.66		FI(3)R 6s	3	1	Red □ on pile	
4374.16	- No. 17	45 50.12 170 35.52		QG	3	1	Green △ on green pile beacon	
4374.18	- No. 18	45 50.20 170 35.54		QR	3	1	Red □ on pile	
4374.2	- No. 19	45 50.17 170 35.44		Iso G 4s	3	1	Green △ on green pile beacon	
4374.22	- No. 20	45 50.29 170 35.45		FI(2)R 5s	3	1	Red □ on pile	
4374.24	- No. 21	45 50.25 170 35.36		FI(2)G 5s	3	1	Green △ on green pile beacon	
4374.26	- No. 22	45 50.40 170 35.37		FI(3)R 6s	3	1	Red □ on pile	
4374.28	- No. 23	45 50.38 170 35.28		FI(3)G 6s	3	1	Green △ on green pile beacon	

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (5)	Elevation metres (6)	Range miles (7)	Structure Height in metres (8)	Remarks (9)
4374.29	- No. 24	45 50.49 170 35.32		QR	3	1	Red □ on red beacon	
4374.3	- No. 25	45 50.47 170 35.23		QG	3	1	Green △ on green beacon	
4374.31	- No. 26	45 50.67 170 35.24		Fl(2)R 5s	3	1	Red □ on double pile beacon	
4374.32	- No. 27	45 50.65 170 35.16		Fl(2)G 5s	3	1	Green △ on green double pile beacon	
4374.33	- No. 28	45 50.83 170 35.15		Fl(3)R 6s	3	1	Red □ on red pile	
4374.34	- No. 29	45 50.80 170 35.08		Fl(3)G 6s	3	1	Green △ on green pile beacon	
4374.36	- No. 30	45 51.01 170 35.03		QR	3	1	Red □ on pile	
4374.38	- No. 31	45 50.98 170 34.96		QG	3	1	Green △ on green pile beacon	
4374.39	- No. 32	45 51.16 170 34.91		Fl(2)R 5s	3	1	Red □ on red beacon	
4374.395	- No. 33	45 51.13 170 34.83		Fl(2)G 5s	3	1	Green △ on green beacon	
4374.4	- No. 34	45 51.28 170 34.81		Fl(3)R 6s	3	1	Red □ on pile	
4374.42	- No. 35	45 51.25 170 34.74		Fl(3)G 6s	3	1	Green △ on green pile beacon	
4374.43	- No. 36	45 51.41 170 34.70		QR	3	1	Red □ on red beacon	
4374.44	- No. 37	45 51.38 170 34.63		QG	3	1	Green △ on green beacon	
4374.45	Beacon at Burkes	45 51.36 170 34.58		Fl Y	2		Yellow X on pile	
4374.46	- No. 38	45 51.53 170 34.59		Fl(2)R 5s	3	1	Red □ on pile	
4374.47	- No. 39	45 51.49 170 34.52		Fl(2)G 5s	3	1	Green △ on green beacon	
4374.48	- No. 40	45 51.70 170 34.43		Fl(3)R 6s	3	1	Red □ on red pile white band	Marks telegraph cable
4374.5	- No. 41	45 51.66 170 34.34		Fl(3)G 6s	3	1	Green △ on green pile beacon, white band	Marks telegraph cable
4374.52	- No. 42	45 51.85 170 34.21		QR	3	1	Red □ on red double pile beacon	
4374.54	- No. 43	45 51.80 170 34.13		QG	3	1	Green △ on green double pile beacon	
4374.55	- No. 44	45 51.95 170 33.99		Fl(2)R 5s	3	1	Red □ on red pile	
4374.56	- No. 45	45 51.89 170 33.94		Fl(2)G 5s	3	1	Green △ on green pile beacon	
4374.58	- No. 46	45 52.03 170 33.78		Fl(3)R 6s	3	1	Red □ on red pile	
4374.6	- No. 47	45 51.97 170 33.74		Fl(3)G 6s	3	1	Green △ on green pile beacon	
4374.61	- No. 48	45 52.08 170 33.63		QR	3	1	Red □ on red pile	
4374.615	- No. 49	45 52.02 170 33.60		QG	3	1	Green △ on green beacon	
4374.62	- No. 50	45 52.11 170 33.50		Fl(2)R 5s	3	1	Red □ on pile	
4374.64	- No. 51	45 52.00 170 33.45		Fl(2)G 5s	3	1	Green △ on green pile beacon	
4374.65	- No. 52	45 52.16 170 33.33		Fl(3)R 6s	3	1	Red □ on red beacon	
4374.655	- No. 53	45 52.11 170 33.29		Fl(3)G 6s	3	1	Green △ on green beacon	
4374.66	- No. 54	45 52.21 170 33.12		QR	3	1	Red □ on red beacon	
4374.68	- No. 55	45 52.16 170 33.07		QG	3	1	Green △ on green double pile beacon	
4374.7	- No. 56	45 52.26 170 32.88		Fl(2)R 5s	3	1	Red □ on pile	
4374.72	- No. 57	45 52.19 170 32.84		Fl(2)G 5s	3	1	Green △ on green pile beacon	

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
4374.725	Ravensbourne Wharf - E end	45 52.22 170 32.69		F G	3	1		Neon □
4374.73	- Centre	45 52.24 170 32.63		2 F G(vert)	3	1		
4374.735	- W end	45 52.25 170 32.57		F G	3	1		Neon □
4374.74	- No. 58	45 52.36 170 32.43		Fl(3)R 6s	3	1	Red □ on pile	
4374.76	- No. 59	45 52.29 170 32.41		Fl(3)G 6s	3	1	Green △ on green pile beacon	
4374.77	- No. 60	45 52.40 170 32.21		Q R	3	1	Red □ on red pile	
4374.78	- No. 61	45 52.35 170 32.19		Q G	3	1	Green △ on green pile beacon	
4374.8	- No. 62	45 52.45 170 31.98		Fl(2)R 5s	3	1	Red □ on pile	
4374.82	- No. 63	45 52.41 170 31.96		Fl(2)G 5s	3	1	Green △ on green pile beacon	
4374.83	- No. 64	45 52.50 170 31.76		Fl(3)R 6s	3	1	Red □ on pile	
4374.84	- No. 66	45 52.54 170 31.58		Q R	3	1	Red □ on pile	
4374.86	- No. 67	45 52.47 170 31.65		Q G	3	1	Green △ on green pile beacon	
4374.88	- No. 68	45 52.58 170 31.41		Fl(2)R 5s	3	1	Red □ on pile	
4374.9	LPG Wharf - E	45 52.45 170 31.54		F G	2	1	On E dolphin	Neon □
4374.91	- Leith Wharf. Head	45 52.43 170 31.43		F G	3	1	E end, side of pumphouse	Neon □
4374.96	- Oil Jetty. Head	45 52.47 170 31.28		2 F G(vert)	9		5	
DUNEDIN								
4374.98	- No. 70	45 52.61 170 31.27		Fl(3)R 6s	3	1	Red □ on pile	
4375	- No. 72	45 52.65 170 31.15		Q R	3	1	Red □ on pile beacon	
4375.02	- No. 74	45 52.74 170 30.97		Fl(2)R 5s	3	1	Red □ on pile	
4375.1	- No. 76	45 52.85 170 30.76		Fl(3)R 6s	3	1	Red □ on pile	
4375.2	- Rattray St Wharf. E end	45 52.72 170 30.79		2 F G(vert)	17	1	Shed	
4375.5	Birch Street Wharf. E end	45 52.84 170 30.66		F G				
4376	Cape Saunders S end (M)	45 52.87 170 43.72		LFI W 10s	58	10	White metal tower 4	fl 2. Vis 254°-064° (170°)
4380	Nugget Point. E end (M)	46 26.91 169 49.11		LFI(2)W 12s	75	14	White stone tower 9	fl 2, ec 2, fl 2, ec 6
4381	Tautuku Peninsula (M)	46 36.8 169 26.3		Fl(3)W 15s	32	8	White metal tower 4	(fl 0.5, ec 1.5) x 2, fl 0.5, ec 10.5
4382	Slope Point (M)	46 40.5 169 00.0		FI W 5s	33	8	White round metal tower 3	fl 1. Vis 268°-098° (190°)
4384	Waipapa Point (M)	46 39.8 168 50.7		Fl(5)W 20s	21	9	White wooden tower 13	(fl 1, ec 1) x 4, fl 1, ec 11
4387	Bushy Point (M)	46 36.5 168 31.2		Fl(2)W 15s	7	8	White metal tower 4	fl 1, ec 2, fl 1, ec 11
STEWART ISLAND / RAKIURA								
4388	Ackers Point (M)	46 53.74 168 09.81		Fl(3)WR 10s	20	W7 R4	White metal tower 5	(fl 0.5, ec 1.5) x 2, fl 0.5, ec 5.5. W 106°-251.7° (145.7°), R 251.7°-257° (5.3°), W 257°-020° (123°). Partially obscured by land 020°-106° (86°)
4389	Halfmoon Bay	46 53.83 168 08.14		Fl R 5s	2	5	Red □ on red metal pile	

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
4394	Dog Island (M)	46 39.2 168 24.6		FlW 10s	46	19	White round stone tower, black bands 37	fl 0.1
	- Reserve light					10		
BLUFF HARBOUR								
4397	- Entrance Light	46 37.5 168 20.5		FlWR 3s	19	W11 R8	White Δ on wooden tower 6	fl 1. R 247.5°-342° (94.5°), W 342°-077.5° (95.5°)
4398	- Stirling Point	46 36.8 168 21.6		F R	11	6	On old signal station roof 7	
4400	- No. 1 Reach. Ldg Lts 031° 00'. Front	46 36.3 168 22.4		F G	6	10	White metal framework pyramid tower 4	Neon \square F R light on water tower 11.8M N
				<i>By day</i>		2		
4400.1	- - Rear. 0.59 M from front			F G	12	12	White metal framework pyramid tower 12	Neon \square
				<i>By day</i>		3		
4402	- No. 2 Reach. Ldg Lts 351°. Front	46 36.03 168 21.65		F R	6	4	White triangular structure	Neon \square
4402.1	- - - Rear. 200 m from front	46 35.92 168 21.63		F R	8	4	White triangular structure	Neon \square
4404	- Ldg Lts 133° 25'. Front. Inner Davey	46 36.34 168 21.87		QW	3	5	White structure on black dolphin	fl 0.3
4404.1	- - - Rear. 235 m from front. Outer Davey Beacon	46 36.43 168 22.00		Iso W 2s	6	5	White structure on black dolphin	
4405	- No. 3 Reach. Ldg Lts 313° 25'. Front	46 35.52 168 20.61		Iso G 2s	7	5	White tower on pile beacon	fl 0.5
4405.1	- - - Rear. 335 m from front			FlW 1.5s	12	5	White tower on metal structure	fl 0.5. Vis 043.5°-223.5° (180°)
4406	- No. 1	46 36.18 168 21.70		FlG 3s	3	2	Green beacon	fl 0.5
4407	- Channel Rocks Beacon	46 36.2 168 21.5		FlR 2s	7	3	Red pile beacon	fl 0.7
4408	- No. 2	46 36.0 168 21.5		Q(2)G 3s	5	2	Green pile beacon	fl 0.3, ec 0.7, fl 0.3, ec 1.7
4410	- Argyle Beacon	46 36.03 168 21.32		Q(2)R 5s	5	3	Red \square on red pile beacon	fl 0.3, ec 0.7, fl 0.3, ec 3.7
4411	- Tidal Beacon	46 36.0 168 21.2		QR	6	2	Red pile beacon	fl 0.3
4413	- No. 3	46 35.86 168 21.20		Fl(3)G 6s	6	3	Green pile beacon	(fl 0.5, ec 1) x 2, fl 0.5, ec 2.5
4415	- No. 4	46 35.8 168 21.2		QG	3	2	Green pile beacon	fl 0.3
4424	- Ldg Lts 279° 01'. Front	46 35.52 168 19.95		F G			White ∇	Neon \square
4424.1	- - Rear. 21 m from front	46 35.52 168 19.94		F G			White ∇	Neon \square
RIVERTON / APARIMA								
4432	- Howells Point/Taramea	46 23.05 168 01.83		FlWR 5s	28	W9 R6	White column 4	fl 1. W shore-298°, R 298°-317° (19°), W 317°-009.5° (52.5°), R 009.5°-shore
4433	Jacobs River Estuary No. 1 Reach. Ldg Lts 307° 12'. Front	46 21.4 168 01.5		F G	5	2	White Δ on beacon 3	Neon \square
4433.1	- - - Rear. 46 m from front			F R	5	2	White ∇ on beacon 3	Neon \square
4434	- No. 2 Reach. Ldg Lts 249° 26'. Front	46 21.7 168 01.3		F R	3	2	White Δ on beacon 3	Neon \square
4434.1	- - - Rear. 19 m from front			F G	3	2	Red ∇ on beacon 3	Neon \square
4435	The Pearl	46 21.6 168 01.1		QR	3	2	Grey beacon 3	

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (4)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
FOVEAUX STRAIT								
4438	Rarotoka Island (Centre Island) S end (M)	46 27.60 167 50.67		FIWR 15s	81	W19 R15	White wooden tower 12	<i>fl 0.1, ec 14.9.</i> R 191°-299° (108°), W 299°-114° (175°), R 114°-141° (27°)
	-- Reserve light					W10 R7		
4440	Long Point (M)	46 15.35 167 06.44		FI(4)W 15s	23	12	Aluminium tower 4	<i>(fl 1, ec 1) x 3, fl 1, ec 8</i>
4442	Puysegur Point (M)	46 09.37 166 36.57		FIW 12s	45	19	White metal tower 5	<i>fl 0.1</i>
	-- Reserve light					10		
4444	Cape Providence (M)	45 59.92 166 27.10		FIW 5s	60	9	White fibreglass tower 4	<i>fl 1</i>
FIORDLAND								
4446	Five Fingers Point (M)	45 43.81 166 27.61		FI(3)W 20s	166	9	Metal framework tower 9	<i>(fl 1, ec 1) x 2, fl 1, ec 15</i>
4452	Secretary Island - SW Point (M)	45 13.48 166 52.41		FI(2)W 15s	52	9	Aluminium pedestal 2	<i>fl 1, ec 2, fl 1, ec 11.</i> Vis 007°-207° (200°)
MILFORD SOUND/PIOPIOTAHU								
4464	- Saint Anne Point (M)	44 34.38 167 46.87		FIW 5s	27	8	White tower 6	<i>fl 1.</i> Vis 071°-316° (245°)
4464.5	- Harrison Cove. Underwater Observatory	44 37.70 167 54.26		QR				
4465	- Deep Water Basin (M)	44 40.69 167 54.83		Q(2)W 5s	2	5	Grey metal pile 3	<i>fl 0.3, ec 0.7, fl 0.3, ec 3.7</i>
4465.2	-- No.6 (M)	44 40.66 167 54.86		FIR 4s	2	1	Red □ on metal pile 6	<i>fl 0.3, ec 3.7</i>
4465.5	- Fresh Water Basin. Breakwater Head	44 40.9 167 55.8		2 F G(vert)	5	1	White metal post 3	1m apart
JACKSON BAY / OKAHU								
4466	Jackson Head (M)	43 57.7 168 37.3		Q(2)W 15s	155	9	White metal tower 4	<i>fl 0.5, ec 0.5, fl 0.5, ec 13.5.</i> Obscured from westward; from shore to 091°
4468	Heretaniwha Point (M)	43 35.3 169 33.2		Q(3)W 10s	77	9	White fibreglass tower	<i>(fl 0.5, ec 0.5) x 2, fl 0.5, ec 7.5</i>
GREYMOUTH HARBOUR								
4470	- S breakwater. 47 m from head	42 26.40 171 11.42		LFIW 10s	17	9	White wooden pole	<i>fl 3.5. Vis 016°-196° (180°)</i> F R lights on radio mast 20 M SSW
4472	-- 32 m from head	42 26.40 171 11.41		FG	11	3	White concrete column	
4473	- N breakwater. Head	42 26.32 171 11.50		FR	11	3	White concrete column	
4475	- Main Ldg Lts 128° 06'. Richmond Quay. Front	42 26.77 171 12.13		F RGR	14		Yellow △ on tower, black diamond on each side 14	Neon □. F R Neon □ on each side, (in line with rear light indicates limits of channel). Channel liable to change
4475.1	-- Rear. 160 m from front	42 26.82 171 12.22		FG	19		White △ on beacon 19	Neon □. Conspicuous from SW.
4476	- Tidal Wall. 27 m from head	42 26.50 171 11.75		QR	5	3	Metal pile 3	
4478	- Main Wharf. Head	42 26.72 171 12.02		FI(2+1)G 6s	5	1	Green wooden pile, red band 2	<i>fl 0.3, ec 0.4, fl 0.3, ec 1.2,</i> <i>fl 0.3, ec 3.5</i>
WESTPORT AND BULLER RIVER								
4486	Cape Foulwind (M)	41 44.95 171 27.93		FIW 12s	70	9	White concrete tower 9	<i>fl 1.2</i>
4490	- W breakwater	41 43.80 171 35.25		FIW 5s	20	6	White square tower, with red band	<i>fl 1</i>
4491	- W breakwater head	41 43.66 171 35.22		FIG 2s	9	5	White round tower with green band 5	<i>fl 0.5</i>
4492	- E breakwater head	41 43.64 171 35.36		FIR 2s	9	5	White round tower with red band at top 5	<i>fl 0.5</i>

SOUTH ISLAND

Int. K No. (1)	Location – Name (2)	Lat Long (3)	S E (3)	Characteristics (4)	Elevation metres (5)	Range miles (6)	Structure Height in metres (7)	Remarks (8)
4494	- Outer Ldg Lts 165° 35'. Front	41 44.21 171 35.49		FG	10		Red X on steel column with yellow fluorescent reflective panels 6	Neon □. Channel liable to change
4494.1	- - Rear. 360 m from front	41 44.38 171 35.55		FG	15		Red ◇ on □ frame red and white vertical bands, orange fluorescent reflective □ panels 11	Neon □
4496	- Inner Ldg Lts 169° 42'. Front	41 44.84 171 35.57		QR	4		Beacon, red and white horizontal bands	
4496.1	- - Rear. 213 m from front	41 44.95 171 35.60		LFIR 5s	7		Beacon, red and white horizontal bands 2	fl 2
4496.5	- E limit transit beacon	41 44.23 171 35.50		FR	11		Pole with black and white bands	Neon □
4496.6	- Broad E pole	41 44.23 171 35.50		FBu	11		Pole with black and white bands	Neon □
4497	- Horse Box	41 44.26 171 35.38		Q(3)G 5s	6		Tripod with black and white metal tower 6	fl 0.5
4499	- Crane Wharf Hd	41 44.72 171 35.67		FR	5	1		Vis 105°-160° (55°)
4506	Kahurangi Point (M)	40 46.7 172 13.2		Fl(2)W 15s	46	9	White metal tower 18	fl 1, ec 2, fl 1, ec 11