

Ruling on cadastral survey network marks

LINZR65302

Purpose of ruling	This ruling specifies the survey marks that are suitable to be used as cadastral survey network marks in cadastral surveys.
Related rules in Rules for Cadastral Survey 2010	<p>4.2 Horizontal datum – connection</p> <p>7.3.2(b) Number and distance of witness marks</p> <p>7.4.2(b) Distances between permanent reference marks and a boundary point</p>
Terms and definitions	<p>As defined in rule 2 of the Rules for Cadastral Survey 2010 (Rules):</p> <ul style="list-style-type: none"> • 'Rules' means Rules for Cadastral Survey 2010, and • 'cadastral survey network mark' means a survey mark of a class specified by the Surveyor-General as suitable for the connection of a cadastral survey to the national survey control network.
Cadastral survey network mark	<ul style="list-style-type: none"> • A survey mark is suitable for use as a cadastral survey network mark if it has been assigned a NZGD2000 coordinate with a Landonline order 6 or better. • Landonline orders are defined in <i>LINZS25006: Standard for tiers, classes, and orders of LINZ data</i>.
Related documents	<p>LINZ 2009, <i>LINZS25006: Standard for tiers, classes, and orders of LINZ data</i>, Office of the Surveyor-General, LINZ, Wellington</p> <p>LINZ 2010, <i>LINZS65000: Rules for Cadastral Survey 2010</i>, Office of the Surveyor-General, LINZ, Wellington</p>